PRESSURE WASHERS

DESIGNED TO EXCEL UNDER PRESSURE.

With models ranging from 2500 to 4000 psi, and featuring reliable Honda engines, there's a New Holland pressure washer for every application. Easily blast dirt from agricultural equipment, tillage machines and much more.

SPECIFICATIONS	MN4013HA	MN2565HA	MN275HX
Engine	Honda OHV GX390	Honda OHV GX200	Honda OHC GC160
PSI	4000	2500	2700
GPM	4.0	3.0	2.3
Torque (ft-lbs, gross)	19.5	9.1	6.9
Displacement	389cc	196cc	160cc
Fuel Tank Capacity	6.1L (1.6 gal.)	3.1L (0.82 gal.)	1.8L (0.47 gal.)
Pump Type	Triplex Plunger Pump AR-RSV4G40	Triplex Plunger Pump AR-RCV3G25	Axial Pump RX705
Spray Tip/Type	Quick Connect	Quick Connect	Quick Connect
# of Spray Nozzles	4 nozzles (0°, 15°, 40°, Soaper)	4 nozzles (0°, 15°, 40°, Soaper)	4 nozzles (0°, 15°, 40°, Soaper)
Soap Injector	Low Pressure	Low Pressure	Low Pressure
Hose Length (ft)	50' Hose	25' Hose	25' Hose
Weight	155 lbs.	85 lbs.	75 lbs.
FEATURES	**MN4013HA**	**MN2565HA**	**MN275HX**
OHV engine	•	•	
Low Oil Shutdown	•	•	
Adjustable Pressure Regulation	•	•	•
Thermal Protection	•	•	•
Cold Water	•	•	•
WARRANTY	**MN4013HA**	**MN2565HA**	**MN275HX**
Engine	3-year limited warranty at Honda Dealers	3-year limited warranty at Honda Dealers	2-year limited warranty at Honda Dealers
Pump	5-year limited warranty	5-year limited warranty	1-year full warranty
Accessories	6-month full warranty	6-month full warranty	6-month full warranty

Powered by HONDA ENGINES

ANNOVI REVERBERI PUMPS

CNH ORIGINAL PARTS

NEW HOLLAND AGRICULTURE

FARM RAISED™

PRESSURE WASHERS

DESIGNED TO EXCEL UNDER PRESSURE.

With models ranging from 1100 to 4000 psi, and featuring reliable PowerEase and Baldor engines, there's a New Holland pressure washer for every application. Easily blast dirt from agricultural equipment, tillage machines and much more.

	GAS ENGINE		ELECTRIC ENGINE
SPECIFICATIONS	**MN4015RA**	**MN317RX**	**MN1115BA**
Engine	Powerease 15HP OHV R240	Powerease 7HP OHV R210	Baldor TEFC 1.5HP
Voltage	N/A	N/A	110V
Amps	N/A	N/A	13.2A
PSI	4000	3100	1100
GPM	4.0	2.3	2.0
Torque (ft-lbs, gross)	19	9	N/A
Displacement	420cc	212cc	N/A
Fuel Tank Capacity	6.7L (1.8 gal.)	3.6L (0.95 gal.)	N/A
Pump Type	Triplex Plunger Pump AR-RSV4640	Axial Pump RX705	Triplex Plunger Pump AR-RCV2G25E
Spray Tip/Type	Quick Connect	Quick Connect	Quick Connect
# of Spray Nozzles	4 nozzles (0°, 15°, 40°, Soaper)	4 nozzles (0°, 15°, 40°, Soaper)	4 nozzles (0°, 15°, 40°, Soaper)
Soap Injector	Low Pressure	Low Pressure	Low Pressure
Hose Length (ft)	50' Hose	25' Hose	25' Hose
Weight	155 lbs.	80 lbs.	84 lbs.
FEATURES	**MN4015RA**	**MN317RX**	**MN1115BA**
OHV engine	•	•	N/A
Low Oil Shutdown	•	•	N/A
Adjustable Pressure Regulation	•	•	•
Thermal Protection	•	•	•
Cold Water	•	•	•
WARRANTY	**MN4015RA**	**MN317RX**	**MN1115BA**
Engine	2-year limited warranty	2-year limited warranty	2-year motor warranty
Pump	1-year full warranty	1-year full warranty	5-year limited warranty
Accessories	6-month full warranty	6-month full warranty	6-month full warranty

PowerEase engines

ANNOVI REVERBERI PUMPS

BALDOR MOTORS AND DRIVES

NEED BALDOR LOGO

CNH ORIGINAL PARTS

NEW HOLLAND AGRICULTURE

FARM RAISED™

© 2011 CNH America LLC. All rights reserved. CNH and New Holland are registered trademarks of CNH America LLC. PM-15405